


UCS60-1H12V (107200390101)

Product Feature

- A channel constant voltage output
- Applicable to indoor LED lights
- Small size, high efficiency, high reliability and long life time
- -25°C~+50°C, working temp
- Protections: overload, overvoltage, short circuit self-recovery protection
- Compliance with CE and ROHS
- 100% Full load aging test
- The warranty period is 5 Years




Application



Technical Parameters

| Model | UCS60-1H12V | |
|------------|-------------------------|---|
| Input | Efficiency | 90%@220VAC, Full load |
| | Voltage | 220VAC-240VAC |
| | Frequency | 50-60Hz |
| | Power Factor | >0.95 |
| | Current | 0.35Amax@220VAC |
| | THD | <15% (at 220V, 50Hz, full load) |
| | Inrush Current | Cold start <60A @200VAC(full load) |
| Output | Current/Voltage/Power | 5A/12VDC/60W |
| | Channel | 1 |
| | Voltage Tolerance | ±5% |
| Protection | Short Circuit | Hiccup, remove fault and recover |
| | Over Voltage | Hiccup, remove fault and recover |
| | Over Current | Hiccup, remove fault and recover |
| Others | Working Temp. | -20°C~+50°C |
| | Storage Temp.; Humidity | -40°C~85°C, 20-90%RH |
| | Tc | 90°C |
| | Material | PC |
| | IP Rating | IP20 |
| | Lifetime | 50,000h@ta:40°C |
| | Warranty Condition | 5 Years |
| | Switch Cycle | >25,000 times |
| | Packing Size | Net weight: 160g±5%/PCS; 50PCS/Carton; 8.5kg±5%/Carton; Carton Size: 435*346*100mm(L*W*H) |
| Dimension | 312*30*18mm(L*W*H) | |


Dimension(mm)



Wiring Diagram




Derating Curve



Cautions

- 1.The product shall be installed and serviced by a qualified person.
- 2.This product is non-waterproof. Please avoid the sun and rain. When installed outdoors please ensure it is mounted in a water proof enclosure.
- 3.Good heat dissipation will prolong the working life of the controller. Please ensure good ventilation.
- 4.Please check if the output voltage and current of any LED power supplies used comply with the requirement of the product.
- 5.Please ensure that adequate sized cable is used from the controller to the LED lights to carry the current. Please also ensure that the cable is secured tightly in the connector.
- 6.For safety consideration, PVC or rubber cord of 0.75-1.5mm² is recommended for input and output terminal(s) .Flat power cord is not suitable. Ensure all wire connections and polarities are correct before applying power to avoid any damages to the LED lights.
- 7.The power supply should be strictly and reliably grounded to prevent electric shock.
- 8.If a fault occurs please return the product to your supplier. Do not attempt to fix this product by yourself.



※ The contents of this manual are updated without prior notice. If the function of the product you are using is inconsistent with the instructions, the function of the product shall prevail. Please contact us if you have any questions.

UCS60-1H12V (107200390101)

产品特点

- 单通道恒压输出
- 适用于LED室内灯具
- 小体积、高效率、高可靠、长寿命;
- 在-20°C~+50°C工作正常;
- 保护种类: 过载、过压、短路自恢复保护;
- 符合CE认证, 符合RoHS环保标准;
- 100%满载老化测试;
- 保固期5年;




应用



技术参数

| 型号 | UCS60-1H12V | |
|----|-------------|--|
| 输入 | 效率 | 90%@220VAC, 满载 |
| | 电压 | 220VAC-240VAC |
| | 频率 | 50-60Hz |
| | 功率因数 | >0.95 |
| | 电流 | 0.35Amax@220VAC, 满载 |
| | THD | <15%[at 220V, 50Hz, 满载] |
| | 浪涌电流 | 冷启动 <60A @200VAC[满载] |
| 输出 | 电流/电压/功率 | 5A/12VDC/60W |
| | 通道 | 1 |
| | 电压公差 | ±5% |
| 保护 | 短路 | 打嗝, 移除故障后自恢复 |
| | 过压 | 打嗝, 移除故障后自恢复 |
| | 过流 | 打嗝, 移除故障后自恢复 |
| 其它 | 工作温度 | -20°C-50°C |
| | 储存温度、湿度 | -40°C-85°C, 20-90%RH |
| | Tc | 90°C |
| | 材质 | PC |
| | 防水等级 | IP20 |
| | 寿命 | 50,000h@ta:40°C |
| | 质保 | 5年 |
| | 开关周期 | >25,000次 |
| | 包装重量 | 净重: 160g±5%/个; 50个/箱; 8.5kg±5%/箱; 外箱尺寸: 435*346*100mm[长*宽*高] |
| | 产品尺寸 | 312*30*18mm[长*宽*高] |


产品尺寸(mm)



应用接线图




降额曲线



注意事项

- 1、本产品请由具有专业资格的人员进行调试安装。
- 2、本产品不能防水，需避免日晒雨淋，如安装在户外，请用防水箱。
- 3、良好的散热条件会延长产品的使用寿命，请把产品安装在通风良好的环境。
- 4、请检查使用的LED电源输出电压电流，是否符合产品要求。
- 5、使用的电线直径大小必须能够负载连接的LED灯具，并确保接线牢固，以免电线过热或接触不良触发事故。
- 6、通电调试前，应确保所有接线正确，以避免因接线错误而导致灯具损坏。
- 7、安装在金属表面，电源应严格可靠接地，以防漏电触电。
- 8、如果发生故障，请勿私自维修；如有疑问，请联系供应商。



※ 本说明书内容如有更新，恕不另行通知。若您使用的产品功能与说明书不一致时，请以产品为准。如有疑问请与我们联系。